

Standard Range Receivers



Features:

- Utilizing secure Code-Hopping Encryption
- Latch or Momentary Relay contacts are selectable via a jumper
- Selectable 1 or 3 second momentary output
- Onboard buzzer sounds on activation and program modes
- Frequencies available are 403.55MHz and 433.92MHz
- 12V or 24V power input requirement
- Compact housing
- The unit can be "Defaulted" via the program jumper

Applications:

- Gate and Garage Door Access Control
- Panic Activation in close range areas
- Arming / Disarming Alarm Systems
- Switching On / Off Security Lighting
- Machinery Control

Specifications:

Encryption Type:.....Code-Hopping
Receiving Range:.....100m (line-of-site)
Frequency - Standard:.....403.55MHz
 - Special:.....433.92MHz
Memory Capacity:.....32 per Channel
Voltage Range:.....10V to 26V DC
Dimensions (lxbxh):.....101 x 63 x 25mm
Gross Weight:.....95 grams
Current Draw:.....15mA
Operating Temp:.....0°C to 49°C

Certifications:

EN300-220 Nov-1997


SABS ETSI EN301-489-1:2001

SABS IEC 60950:1999

ICASA: TA-2006/759



RX1-100



RX2-100

Order Codes:

1-Channel Receiver: 100m	RX1-100
2-Channel Receiver: 100m	RX2-100